

# PC 5638 18 T



Sample image

**Order symbol :** PC 5638 18 T

**Product nr :** 5330065

UL Name : UL PC 5638 18 T

**Description :** Enclosure, PC

**Remarks :** Transparent cover


**EAN :** 6418074005618

**El. number :**

- Finland : 3423823
- Denmark : 8212051904
- Sweden : 2539458

**Including :** Base with screws for mounting plate. cover with PUR gasket and polyamide cover screws.

SOLID 558x378x180



**Dimensions :**

mm :

**Height**

560

**Width**

380

**Depth**

180

**Accessories :**

EKUVT Mounting plate, for enclosures:

inch : 22.05 14.96 7.09

**Materials :**

Material : Polycarbonate  
Base colour : RAL\_7035  
Cover colour : Clear transparent  
Gasket material : Polyurethane

**Temperatures :**

Temperature °C (continuous) : -40 ... 80  
Temperature °F (continuous) : -40 ... 175

(518 x 338 x 1.5)

EKV 32 DIN-35 Mounting rail, for enclosures:  
(335 x 35 x 7.5)

EKUZR Extension frame, for enclosures:  
(560 x 380 x 50)

**Ratings :**

Ingress protection (EN 60529): IP66; IP67;  
Impact Resistance (EN 62262): IK08;  
electrical\_insulation : Totally insulated  
Halogen free (DIN/VDE 0472, Part 815) : Yes  
UV resistance : UL 746C  
Flammability Rating : UL 94 V0  
Glow Wire Test (IEC 695-2-1) °C : 960C

**Certificates :**

DSS\_FI\_41597\_A1